

C16 CONSTRUCTION TIMBERS PRICE LIST

RETAIL

C16 TIMBER



C16 is the most commonly used form of timber, it can be used in many different applications and is the most cost effective option.

C16 timbers are kiln dried to minimise the amount of moisture in the wood. This grade of timber which is commonly used in internal construction such as floors, walls and roof joists is not only cost effective, it has the strength and other properties such as bending, compression and density which are required for construction.

As strong, versatile and cost effective this grade of timber might be, it does have some defects, such as, grain deviations which may effect the strength of the timber as well as some cosmetic defects such as sap stains and sometimes an uneven surface.

Section (in/mm)	Grade	Length (m)
2 x 2	No Grade	2.4
50 x 47	No Grade	3.0
3 x 2	C16	1.8
75 x 47		2.4
		3.0
		3.6
		4.8
4 x 2	C16	1.8
100 x 47		2.4
		3.0
		3.6
		4.8
5 x 2	C16	3.6
125 x 47		
6 x 2	C16	3.6
150 x 47		4.8
8 x 2	C16	3.6
200 x 47		4.8

ALL PRICES SUBJECT TO VAT



CONTACT US

01543 425893 / info@treeway.co.uk

Cannock Wood Industrial Estate . Cannock Wood Street . Cannock . Staffordshire . WS12 0PL
www.treeway.co.uk



TFRF26